

aeOLUS

2013

Quality Speaks all Languages



NEW ZEALANDS BEST VALUE COMMERCIAL TYRE BRAND



VISION

Aeolus is New Zealand and the South Pacific's largest direct to market tire importer and wholesaler.

Our employees all have a passion for the industry and act with integrity. We exist to provide an excellent product at a fair price.

Aeolus NZ Ltd

General Manager
Tex Wright

0800 AEOLUS




HN805

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
265/70R19.5	18 7.5	258	866	2725	2575	900	900	143/141J
385/55R22.5	20 12.25	391	996	4250		830		158L 160J
385/65R22.5	18 11.75	385	1070	4250		830		158L 160J


 STEER
  TRAILER

Wide shoulders for superior lateral stability and resistance to curbing damage. Low rolling resistance for reduced road noise and superior efficiency. Sipes provide enhanced hydroplaning resistance.




ADR69 HN369

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
295/80R22.5	18 9.00	244		3550	3250	900	790	152/148M



 DRIVE

Excellent traction design for on the highway. Wide and deep tread design provides notable anti-irregular wearing. M+S Pattern for powerful grip ability and good traction character



HN267

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1051	3000	2725	830	830	146/143M


 STEER
  TRAILER

All position, premium line-haul steer. Multi angled grooving improves overall traction, enhanced wear and durability. Added decoupling groove, optimising anti-side-skid in all weather conditions. Wide shoulder design for stability and tire longevity.




HN308

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1062	3000	2725	830	830	146/143L
275/80R22.5	16 8.25	285	1026	3075	2800	830	830	149/146L


 STEER
  DRIVE
  TRAILER

Steer or Trailer tyre for long distance application Triple rib design for even load distribution. Staggered deep grooves for exceptional cooling and cut resistance. Solid shoulder provides support in the most demanding haul situations.



HN359

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
305/70R22.5	18 9.00	312	1020	3450	3150	830	830	152/148M

 DRIVE

Long distance drive tyre. Outstanding drainage and anti-side-skid characteristics. M+S Pattern for excellent traction and anti-wearing characteristics.




HN257

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
265/70R19.5	16 7.50	258	866	2500	2360	830	830	140/138M
275/70R22.5	18 8.25	272	963	3150	2900	900	900	148/145M
295/60R22.5	18 9.00	288	916	3250	3000	900	900	149/146L
305/70R22.5	18 9.00	312	1018	3450	3150	830	830	152/148M




 STEER
  TRAILER

Micro-sipes within groove walls for enhanced traction in all weather conditions. Variable tread angles for self-cleaning and stone ejection. Reinforced sidewall for increased tread life.




AGB20 HN226

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25			3000	2725	830	830	148/145J/151/148E
295/80R22.5	18 9.00			3550	3250	900	900	152/148J/154/150E


 STEER
  DRIVE
  TRAILER

Suitable for Steer and Drive axle. Strong carcass design and strengthened sidewalls provides life durability. Wide and deep tread pattern provides superb turning stability.




HN355

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
275/70R22.5	18 8.25	272	972	3150	2900	900	900	148/145M
295/60R22.5	18 9.00	288	925	3250	3000	900	900	149/146L
295/80R22.5	18 9.00	303	1062	3550	3250	900	900	152/148M



 DRIVE

Interlocking tread blocks provide exceptional control and weight distribution. Square footprint for at-speed control and stability. Staggered deep grooves for exceptional cooling and tread life.

ASR69
HN254




SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
295/80R22.5	18 9.00	233	1045	3550	3250	900	790	152/148M



 STEER
 TRAILER

Steer or Trailer wheel, suitable to use on good road condition. Wider tread design, which can provide better antiwearing character and good turning direction stability. Longer mileage and good retreadability.

HN207



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
385/65R22.5	18 11.75							

 STEER
 TRAILER

All position regional use tyre
Zig-zag pattern designed to deliver superior traction and stability. Extra-wide grooved shoulders designed for even weight distribution and resistance to uneven wear. Stone ejectors built into grooves for exceptional stone chipping resistance and excellent tread life

HN230




SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
8.25R15	18 6.50	237	834	2725	2575	850	850	143/141G/141/140J
10.00R15	18 7.50	279	923	3150	3900			148/145G
255/70R22.5	16 17.50	251	925	2500	3200	830	830	140/137M
275/70R22.5	18 8.25	272	963	3150	2900	900	900	148/145M




 STEER
 DRIVE
 TRAILER

Steer/Drive or Trailer wheel
Square footprint for even load distribution. Wide closed shoulders enhance stability and prevent against irregular wear Patterned grooves efficiently channel water for superior wet traction. Low rolling resistance and good high speed character.

HN235




SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
215/75R17.5	18 6.00	215	763	2180	2060	900	900	135/133J
235/75R17.5	18 6.75	240	793	2725	2575	900	900	143/141J



 STEER
 DRIVE
 TRAILER

Staggered tread blocks for superior performance and wet traction. Micro-grooves in tread to prevent against stone cuts. Solid shoulder for lateral stability.

ASR24



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
9.5R 17.5	14 6.75	240	842	1850	1750	760	760	129/127M
9.5R 17.5	18 6.75	240	842	2568	2240	900	900	136/134M

 STEER
 TRAILER

Four rib design with Zig-zag patterns for stone decoupling. Deep arrowhead shoulder grooves for maximum traction in rough terrain situations. Extra-deep tread design and unique compound for extended tread life.

HN366



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
245/70R19.5	16 7.50	248	846	2180	2060	830	830	136/134M/136/135J

 DRIVE

M+S pattern traction Drive tyre.
Tapered tread grooves for enhanced stone ejection and improved tread life
Lateral groove sipes deliver exceptional hydroplaning resistance. Symmetrical tread pattern is optimized increases dry road stability and rough terrain biting.

Gleeson & Cox Transport Limited

We are running Aeolus Tyres across all of our fleet of 75 trucks plus trailers and have been more than impressed with their range and overall performance. The huge saving on our tyre bill by using Aeolus is helpful in this time of unprecedented price increases.


Paul Dragt
Workshop Manager

0800 AEOLUS

AGB20

HN226


SIZE	PLY/RM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25			3000	2725	830	830	148/145/151/148E
295/80R22.5	18 9.00			3550	3250	900	900	152/148/154/150E

 STEER
  DRIVE
  TRAILER

Suitable for Steer and Drive axle.
Strong carcass design and strengthened sidewalls provides life durability.
Wide and deep tread pattern provides superb turning stability.

HN306

SIZE	PLY/RM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1062	3000	2725	830	830	146/143M

 DRIVE

Extra-Strong casing for enhanced durability and excellent re-treadability. Interlocking tread pattern to handle even the most demanding haul applications. Variable tread sipes resist cutting and chunking.

HN805

SIZE	PLY/RM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
265/70R19.5	18 7.5	258	866	2725	2575	900	900	143/141J
385/55R22.5	20 12.25	391	996	4250		830		158L 160J
385/65R22.5	18 11.75	385	1070	4250		830		158L 160J

 STEER
  TRAILER

Wide shoulders for superior lateral stability and resistance to curbing damage. Low rolling resistance for reduced road noise and superior efficiency. Sipes provide enhanced hydroplaning resistance.

HN257

SIZE	PLY/RM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
265/70R19.5	16 7.50	258	866	2500	2360	830	830	140/138M
275/70R22.5	18 8.25	272	963	3150	2900	900	900	148/145M
295/60R22.5	18 9.00	288	916	3250	3000	900	900	149/146L
305/70R22.5	18 9.00	312	1018	3450	3150	830	830	152/148M

 STEER
  TRAILER

Micro-sipes within groove walls for enhanced traction in all weather conditions. Variable tread angles for self-cleaning and stone ejection. Reinforced sidewall for increased tread life.

HN308



SIZE	PLY/RM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1062	3000	2725	830	830	146/143L
275/80R22.5	16 8.25	285	1026	3075	2800	830	830	149/146L

 STEER
  DRIVE
  TRAILER

Steer or Trailer tyre for long distance application
Triple rib design for even load distribution.
Staggered deep grooves for exceptional cooling and cut resistance. Solid shoulder provides support in the most demanding haul situations.

HN207

SIZE	PLY/RM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
385/65R22.5	18 11.75							




 STEER
  TRAILER

All position regional use tyre.
Zig-zag pattern designed to deliver superior traction and stability. Extra-wide grooved shoulders designed for even weight distribution and resistance to uneven wear. Stone ejectors built into grooves for exceptional stone chipping resistance and excellent tread life.

AGC28

HN228




SIZE	PLY/RM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
255/70R19.5	16 7.50	251	932	2500	2300	830	830	140/137L
265/70R19.5	18 7.50	258	866	2725	2575	900	900	143/141J
275/70R22.5	18 8.25	272	968	3150	2900	900	900	148/145L
385/65R22.5	18 11.75	385	1070	4250		830		158L 160J

 STEER
  DRIVE
  TRAILER


Soil and mud traction through angled shoulder snipes. Opposing tread block design reduces chipping and scrape. Superior wet traction through an aggressive shoulder design.

HN235

SIZE	PLY/RM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
215/75R17.5	18 6.00	215	763	2180	2060	900	900	135/133J
235/75R17.5	18 6.75	240	793	2725	2575	900	900	143/141J


 STEER
  DRIVE
  TRAILER

Staggered tread blocks for superior performance and wet traction. Micro-grooves in tread to prevent against stone cuts. Solid shoulder for lateral stability.




HN309

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
235/75R17.5	16 6.75	240	800	2000	1850	830	830	132/129M




 DRIVE

Symmetrical tread design resists tear and chipping and provides road stability. M+S wave pattern sipes enhance hydroplaning resistance and improve lateral biting. Staggered tread blocks deliver exceptional stone ejection and self-cleaning capabilities.




HN230

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
8.25R15	18 6.50	237	834	2725	2575	850	850	143/141G/141/140J
10.00R15	18 7.50	279	923	3150	3900			148/145G
255/70R22.5	16 17.50	251	925	2500	3200	830	830	140/137M
275/70R22.5	18 8.25	272	963	3150	2900	900	900	148/145M




 STEER
 DRIVE
 TRAILER

Steer/Drive or Trailer wheel. Square footprint for even load distribution. Wide closed shoulders enhance stability and prevent against irregular wear. Patterned grooves efficiently channel water for superior wet traction. Low rolling resistance and good high speed character.




HN08

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
7.00R16	available							
7.50R16	14 6.00G	216	803	1500	1320	770	770	122/118L
8.25R16	14 6.50H	234	850	1700	1500	670	670	126/122L
9.00R20	16 7.00	255	1022	2800	2650	900	900	144/142K
10.00R20	16 7.50	270	1052	3000	2630	840	770	146/143K
11R22.5	16 8.25	277	1054	3000	2725	830	830	146/143L
8.25R/20	16 6.50	232	965	2430	2300	930	930	139/137K

 STEER
 DRIVE
 TRAILER


Four rib design with Zig-zag patterns for stone decoupling. Deep arrowhead shoulder grooves for maximum traction in rough terrain situations. Extra-deep tread design and unique compound for extended tread life.




ADC53

HN353

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
13R22.5	18 9.75	316	1136	3750	3450	790	790	154/151G
11R22.5	16 8.25			3000	2725	830	830	146/143G
275/70R22.5	16 8.25	272	972	3150	2900	900	900	148/145L
295/80/22.5	18							
315/80R22.5	18 9.00	315	1088	3750	3450	830	830	154/150M


 DRIVE

Special 18 ply construction for enhanced structural strength. Deep lateral shoulders to enhance water and mud ejection. Directional tread design provides exceptional biting and handling in rough terrains. Angled tread blocks deliver outstanding self-cleaning and extended wear protection.




HN355

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
275/70R22.5	18 8.25	272	972	3150	2900	900	900	148/145M
295/60R22.5	18 9.00	288	925	3250	3000	900	900	149/146L
295/80R22.5	18 9.00	303	1062	3550	3250	900	900	152/148M


 DRIVE

Interlocking tread blocks provide exceptional control and weight distribution. Square footprint for at-speed control and stability. Staggered deep grooves for exceptional cooling and tread life.




HN357

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25			3000	2725	830	830	146/143G



 DRIVE

Extra-deep grooves enhance cooling and provides superior traction in tough rain, mud, and snow conditions. Staggered tread block distributes weight evenly and resisting irregular wear. S-pattern sipes for superior self-cleaning capabilities.




ASR24

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
9.5R 17.5	14 6.75	240	842	1850	1750	760	760	129/127M
9.5R 17.5	18 6.75	240	842	2568	2240	900	900	136/134M




 STEER
 TRAILER

Four rib design with Zig-zag patterns for stone decoupling. Deep arrowhead shoulder grooves for maximum traction in rough terrain situations. Extra-deep tread design and unique compound for extended tread life.




HN266

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1062	3000	2725	830	830	144/148L

 STEER
 DRIVE
 TRAILER

Interlocking honeycomb tread design for exceptional weight distribution and even wear. Open shoulders with extra deep sipes for lateral stability and biting in off-road terrains. 23/32nds tread depth for extra-long tread life. Reinforced casing for excellent off-road performance and longevity.



● STEER

● DRIVE


● TRAILER

AGC28

HN228

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
255/70R19.5	16 7.50	251	932	2500	2300	830	830	140/137L
265/70R19.5	18 7.50	258	866	2725	2575	900	900	143/141J
275/70R22.5	18 8.25	272	968	3150	2900	900	900	148/145L
385/65R22.5	18 11.75	385	1070	4250		830		158L 160J

Soil and mud traction through angled shoulder snipes.
Opposing tread block design reduces chipping and scrape.
Superior wet traction through an aggressive shoulder design.




● DRIVE

ADC53

HN353

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
10.00R20	7.50	270	1055	3000	2630			146/143K
11R22.5	16 8.25	277	1066	3000	2725	830	830	146/143L
275/70R22.5	16 8.25	272	972	3150	2900	900	900	148/145L
295/80/22.5	18							
315/80R22.5	18 9.00	315	1088	3750	3450	830	830	154/150M

Special 18 ply construction for enhanced structural strength. Deep lateral shoulders to enhance water and mud ejection. Directional tread design provides exceptional biting and handling in rough terrains. Angled tread blocks deliver outstanding self-cleaning and extended wear protection.




● DRIVE

HN10

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
10.00R20	16							
11R22.5	16 8.25			3000	2725	830	830	146/143G
13R22.5	18 9.75	316	1136	3750	3450	790	790	154/151G

Suitable drive tyre for extreme terrain applications.
Powerful grip ability and optimal passing through characteristics.
Maximum mileage with enhanced anti-wear and anti-puncture resistance.



● STEER


● DRIVE

● TRAILER

HN08



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
7.00R16	available							
7.50R16	14 600G	216	803	1500	1320	770	770	122/118L
8.25R16	14 6.50H	234	850	1700	1500	670	670	126/122L
8.25R20	16 6.50	232	965	2430	2300	930	930	139/137K
9.00R20	16 7.00	255	1022	2800	2650	900	900	144/142K
10.00R20	16 7.50	270	1052	3000	2630	840	770	146/143K
11R22.5	16 8.25	277	1054	3000	2725	830	830	146/143L
315/80R22.5	20							

Four rib design with Zig-zag patterns for stone decoupling.
Deep arrowhead shoulder grooves for maximum traction in rough terrain situations.
Extra-deep tread design and unique compound for extended tread life.




HN253

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
13R22.5	18							




 STEER
  TRAILER

Suitable for front axle, drive axle and trailer in mixed terrain. Excellent crack and tear resistance. Low heat generating and casing extremely suitable for retreading.




HN266

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1062	3000	2725	830	830	144/148L


 STEER
  DRIVE
  TRAILER

Interlocking honeycomb tread design for exceptional weight distribution and even wear. Open shoulders with extra deep sipes for lateral stability and biting in off-road terrains. 23/32nds tread depth for extra-long tread life. Reinforced casing for excellent off-road performance and longevity.




HN306

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1062	3000	2725	830	830	146/143M


 DRIVE

Extra-Strong Casing for enhanced durability and excellent re-treadability Interlocking tread pattern to handle even the most demanding haul applications. Variable tread sipes resist cutting and chunking.




HN357

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25			3000	2725	830	830	146/143G


 DRIVE

Extra-deep grooves enhance cooling and provides superior traction in tough rain, mud, and snow conditions. Staggered tread block distributes weight evenly and resisting irregular wear. S-pattern sipes for superior self-cleaning capabilities.




HN09

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
8.25R16	14 6.50	234	852	1700	1500	670	670	126/122L
900R20	16							




 DRIVE

DriveTyre suitable for construction zones. Optimum performance in both wet and dry conditions. Excellent passing through characteristics. Anti-crack and puncture resistance.



AGB20 HN226

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD kg	DUAL MAX LOAD kg	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25			3000	2725	830	830	148/145/151/148E
295/80R22.5	18 9.00			3550	3250	900	900	152/148/154/150E

 STEER
  DRIVE
  TRAILER

Suitable for Steer and Drive axle. Strong carcass design and strengthened sidewalls provides life durability. Wide and deep tread pattern provides superb turning stability.

Stan Semenoff Transport Limited

We have been using Aeolus tyres for just on 3 years. During that time we have used steerers, drivers and trailer tyres on our Livestock and Bulk Fleet trucks, which includes on and off highway running, and quarry work.

We would have not normally gone past the premium brands but we are more than happy with the performance in relation to the value for money, and I couldn't see us going back to premium brands.

Stan Semenoff
Managing Director

0800 AEOLUS

BUS

HN226



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25			3000	2725	830	830	148/145J/151/148E
275/70R22.5	18 8.25			3150	2900	900	900	148/145J/152/148E
295/80R22.5	18 9.00			3550	3250	900	900	152/148J/154/150E



STEER



DRIVE



TRAILER

Suitable for Steer and Drive axle.
Strong carcass design and strengthened sidewalls provides life durability. Wide and deep tread pattern provides superb turning stability.

HN306



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1062	3000	2725	830	830	146/143M



DRIVE

Extra-Strong Casing for enhanced durability and excellent re-treadability Interlocking tread pattern to handle even the most demanding haul applications. Variable tread sipes resist cutting and chunking.

HN230



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
8.25R15	18 6.50	237	834	2725	2575	850	850	143/141G/141/140J
10.00R15	18 7.50	279	923	3150	3900			148/145G
255/70R22.5	16 17.50	251	925	2500	3200	830	830	140/137M
275/70R22.5	18 8.25	272	963	3150	2900	900	900	148/145M



STEER



DRIVE



TRAILER

Steer/Drive or Trailer wheel
Square footprint for even load distribution. Wide closed shoulders enhance stability and prevent against irregular wear Patterned grooves efficiently channel water for superior wet traction. Low rolling resistance and good high speed character.

HN257



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
265/70R19.5	16 7.50	258	866	2500	2360	830	830	140/138M
275/70R22.5	18 8.25	272	963	3150	2900	900	900	148/145M
295/60R22.5	18 9.00	288	916	3250	3000	900	900	149/146L
305/70R22.5	18 9.00	312	1018	3450	3150	830	830	152/148M



STEER



TRAILER

Micro-sipes within groove walls for enhanced traction in all weather conditions. Variable tread angles for self-cleaning and stone ejection. Reinforced sidewall for increased tread life.

HN355



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
275/70R22.5	18 8.25	272	972	3150	2900	900	900	148/145M
295/60R22.5	18 9.00	288	925	3250	3000	900	900	149/146L
295/80R22.5	18 9.00	303	1062	3550	3250	900	900	152/148M



DRIVE

Interlocking tread blocks provide exceptional control and weight distribution.
Square footprint for at-speed control and stability. Staggered deep grooves for exceptional cooling and tread life.

HN207



SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
385/65R22.5	18 11.75							



STEER



TRAILER

All position regional use Tyre. Zig-zag pattern designed to deliver superior traction and stability. Extra-wide grooved shoulders designed for even weight distribution and resistance to uneven wear. Stone ejectors built into grooves for exceptional stone chipping resistance and excellent tread life.

HN805



STEER




TRAILER

SIZE

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
265/70R19.5	18 7.50	258	866	2725	2575	900	900	143/141J
385/55R22.5	20 2.25	391	996	4250		830		158L 160J
385/65R22.5	18 11.75	385	1070	4250		830		158L 160J




Wide shoulders for superior lateral stability and resistance to curbing damage.
Low rolling resistance for reduced road noise and superior efficiency.
Sipes provide enhanced hydroplaning resistance.




AGC28

HN228

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
255/70R19.5	16 7.50	251	932	2500	2300	830	830	140/137L
265/70R19.5	18 7.50	258	866	2725	2575	900	900	143/141J
275/70R22.5	18 8.25	272	968	3150	2900	900	900	148/145L
385/65R22.5	18 11.75	385	1070	4250		830		158L 160J




 STEER
  DRIVE
  TRAILER

Soil and mud traction through angled shoulder snipes. Opposing tread block design reduces chipping and scrape. Superior wet traction through an aggressive shoulder design.



HN230

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
8.25R15	18 6.50	237	834	2725	2575	850	850	143/141G/141/140J
10.00R15	18 7.50	279	923	3150	3900			148/145G
255/70R22.5	16 17.50	251	925	2500	3200	830	830	140/137M
275/70R22.5	18 8.25	272	963	3150	2900	900	900	148/145M

 STEER
  DRIVE
  TRAILER

Steer/Drive or Trailer wheel. Square footprint for even load distribution. Wide closed shoulders enhance stability and prevent against irregular wear. Patterned grooves efficiently channel water for superior wet traction. Low rolling resistance and good high speed character.



HN809

 TRAILER



HN805

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
265/70R19.5	18 7.5	258	866	2725	2575	900	900	143/141J
385/55R22.5	20 12.25	391	996	4250		830		158L 160J
385/65R22.5	18 11.75	385	1070	4250		830		158L 160J

 STEER
  TRAILER

Wide shoulders for superior lateral stability and resistance to curbing damage. Low rolling resistance for reduced road noise and superior efficiency. Sipes provide enhanced hydroplaning resistance.



HN235

 STEER
  DRIVE
  TRAILER



HN08

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
7.00R16	available							
7.50R16	14 6.00G	216	803	1500	1320	770	770	122/118L
8.25R16	14 6.50H	234	850	1700	1500	670	670	126/122L
9.00R20	16 7.00	255	1022	2800	2650	900	900	144/142K
10.00R20	16 7.50	270	1052	3000	2630	840	770	146/143K
11R22.5	16 8.25	277	1054	3000	2725	830	830	146/143L
8.25R/20	16 6.50	232	965	2430	2300	930	930	139/137K


 STEER
  DRIVE
  TRAILER

Four rib design with Zig-zag patterns for stone decoupling. Deep arrowhead shoulder grooves for maximum traction in rough terrain situations. Extra-deep tread design and unique compound for extended tread life.





HN253

 STEER
  TRAILER




HN267

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
11R22.5	16 8.25	277	1051	3000	2725	830	830	146/143M



 STEER
  TRAILER

All position, premium line-haul steer. Multi angled grooving improves overall traction, enhanced wear and durability. Added decoupling groove, optimising anti-side-skid in all weather conditions. Wide shoulder design for stability and tire longevity.



HN828

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
225/70R19.5	14	8.90	31.90	3,968@110	3,748@110			128/126M
245/70R19.5	18	9.80	33.10	4,806@120	4,542@120			135/133M


 STEER
  TRAILER

Trailer, long haul tyre. Wide solid shoulders with decoupling groove for enhanced stability under all speed conditions. Symmetrical tread pattern design for even weight distribution and improved lateral stability. Extra-wide grooves channel water into sipes for improved hydroplaning resistance.




HN829

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
435/50R19.5	20 14.00			4500	900			160J
445/45R19.5	22 14.00			4500	900			160J



 TRAILER

Trailer axel.
Newly developed profile with extremely low rolling resistance.
Excellent cost per kilometre.




ASR24

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
9.5R17.5	14 6.75	240	842	1850	1750	760	760	129/127M
9.5R17.5	18 6.75	240	842	2568	2240	900	900	136/134M



 STEER
  TRAILER

Wide shoulders for superior lateral stability and resistance to curbing damage. Low rolling resistance for reduced road noise and superior efficiency. Sipes provide enhanced hydroplaning resistance.




HN257

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
265/70R19.5	16 7.50	258	866	2500	2360	830	830	140/138M
275/70R22.5	18 8.25	272	963	3150	2900	900	900	148/145M
295/60R22.5	18 9.00	288	916	3250	3000	900	900	149/146L
305/70R22.5	18 9.00	312	1018	3450	3150	830	830	152/148M



 STEER
  TRAILER

Micro-sipes within groove walls for enhanced traction in all weather conditions. Variable tread angles for self-cleaning and stone ejection. Reinforced sidewall for increased tread life.




HN207

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
385/65R22.5	18 11.75							


 STEER
  TRAILER

All position regional use Tyre. Zig-zag pattern designed to deliver superior traction and stability. Extra-wide grooved shoulders designed for even weight distribution and resistance to uneven wear. Stone ejectors built into grooves for exceptional stone chipping resistance and excellent tread life.



HN366

SIZE	PLY / RIM	SECTION WIDTH mm	OVERALL DIAMETER mm	SINGLE MAX LOAD KG	DUAL MAX LOAD KG	SINGLE KPA	DUAL KPA	LOAD INDEX / SPEED SYMBOL
245/70R19.5	16 7.50	248	846	2180	2060	830	830	136/134M/136/135J

 DRIVE

M+S pattern traction Drive tyre.
Tapered tread grooves for enhanced stone ejection and improved tread life
Lateral groove sipes deliver exceptional hydroplaning resistance. Symmetrical tread pattern is optimized increases dry road stability and rough terrain biting.

John Fillmore Contracting

We changed over to Aeolus Tyres for all of our 35 trucks in June '08. Since then we have made significant savings (35%) on our tyre costs and puncture repairs. We do not run retreads as they are uneconomical compared to new Aeolus Tyres. We run both steer, drive and trailer tyres.

We are more than happy with the performance of Aeolus Tyres and their value for money.

Sam Fillmore
Director

PATTERN	SIZE	DRIVE	STEER	TRAILER
HN230	8.25R15-18 ply incl kit	✓	✓	✓
HN230	10.00R15-18 ply incl kit	✓	✓	✓
HN08	7.00/16R 14 ply incl kit	✓	✓	✓
HN08	7.50R16-14 ply incl kit	✓	✓	✓
HN09	8.25R/16 14 ply incl kit	✓		
HN08	8.25R16-14 ply incl kit	✓	✓	✓
HN08	8.25R20-16 ply incl kit	✓	✓	✓
HN08	9.00R20-14 ply incl kit	✓	✓	✓
HN09	9.00R20-16 ply incl kit	✓		
HN08	10.00R20-16 ply incl kit	✓	✓	✓
HN10	10.00R20-16 ply incl kit	✓		
HN353	10.00R20-16 ply incl kit	✓		
HN235	215/75R17.5-18 ply	✓	✓	✓
HN235	235/75R17.5-18ply	✓	✓	✓
HN309	235/75R17.5-16 ply	✓		
ASR24	9.5 17.5-14 ply		✓	✓
HN828	225/70R19.5-14 ply		✓	✓
HN366	245/70R19.5-16 ply	✓		
HN828	245/70R19.5-18 ply		✓	✓
HN805	265/70R19.5-18 ply		✓	✓
HN228	265/70R19.5-18 ply	✓	✓	✓
HN257	265/70R19.5-16 ply		✓	✓
HN829	435/50R19.5- 20 ply			✓
HN829	445/45R19.5- 22 ply			✓
HN267	11R 22.5 16 ply		✓	✓
HN308	11R 22.5-16 ply	✓	✓	✓
HN08	11R22.5-16 ply	✓	✓	✓
HN226	11R22.5-16 ply	✓	✓	✓
HN266	11R22.5-16 ply	✓	✓	✓
HN306	11R22.5-16 ply	✓		
HN353	11R22.5-16 ply	✓		
HN357	11R22.5-16 ply	✓		
HN10	11R22.5-16 ply	✓		
HN10	13R22.5 18 ply	✓		
HN253	13R22.5-18 ply		✓	✓
HN228	255/70R22.5-16 ply	✓	✓	✓
HN230	255/70R22.5-16 ply	✓	✓	✓
HN228	275/70R22.5-18 ply	✓	✓	✓
HN230	275/70R22.5-18 ply	✓	✓	✓
HN257	275/70R22.5-18 ply		✓	✓
HN355	275/70R22.5-18 ply	✓		
HN353	275/70R22.5-18 ply	✓		
HN308	275/80R22.5-16 ply	✓	✓	✓
HN257	295/60R22.5-18 ply		✓	✓
HN355	295/60R22.5-18 ply	✓		
AGB20	295/80R22.5-18 ply	✓	✓	✓
HN254	295/80R22.5-18 ply		✓	✓
HN353	295/80R22.5-18 ply	✓		
HN355	295/80R22.5-18 ply	✓		
ADR69	295/80R22.5-18 ply	✓		
ASR69	305/70R22.5-18 ply		✓	✓
HN359	305/70R22.5 18 ply	✓		
HN08	315/80R22.5 20 ply	✓	✓	✓
HN353	315/80R22.5 20 ply	✓		
HN805	385/55R22.5-20 ply		✓	✓
HN207	385/65R22.5-18 ply		✓	✓
AGC28	385/65R22.5-18 ply	✓	✓	✓
HN805	385/65R22.5-18 ply		✓	✓

0800 236 587

www.aeolustyres.co.nz

0800 AEOLUS

NATION WIDE SERVICE NETWORK



‘we’ve got you covered’

• Office Manager	0800 236 587	office@aeolustyres.co.nz
• Internal Sales	0800 236 587	info@aeolustyres.co.nz
• Lower North Island	021 928 815	insales@aeolustyres.co.nz
• Auckland South	021 928 885	sales@aeolustyres.co.nz
• Auckland North	021 928 817	info@aeolustyres.co.nz
• South Island	0800 236 587	info@aeolustyres.co.nz
• Earthmoving	0800 236 587	sales@aeolustyres.co.nz