



# A2235

Usage: applied for cranes in highways  
 Characteristic: with better traction;  
 superior mileage and wear-resisting  
 performance for first using life. With  
 good water draining and side-sliding  
 properties

SIZE	STAR RATING	RIM	NEW TYRE DIMENSION(mm)		LOAD(kg)		PRESSURE(kPa)		LI/SS		TRA CODE	TREAD DEPTH (mm)	VALVE
			WID.	DIA.	10km/	50km/	10km/	50km/h	10km/h	50km/h			
14.00R25 TL	★★★	10.00/1.5	379	1369		6000		900		170E	E-2	23	----
16.00R25 TL	★★	11.25/2.0	435	1481		7300		900		177E	E-2	29.5	HZ01
16.00R25 TL	★★★	11.25/2.0	435	1481		7750		900		179E	E-2	29.5	HZ01

# A2233



Usage: applied for loader,  
 bulldozer as well as earthmover  
 in poor working condition.  
 Characteristics: L5 deep tread  
 pattern with high traction  
 performance, hard and  
 strengthen belt, tyre shoulder,  
 tyre side and tyre crown can  
 provide good cut resistance and  
 anti-pierce. it is suitable for rock  
 road operation requirement.

SIZE	STAR RATING	RIM	NEW TYRE DIMENSION(mm)		LOAD(kg)		PRESSURE(kPa)		LI/SS		TRA CODE	TREAD DEPTH (mm)	VALVE
			WID.	DIA.	10km/h	50km/h	10km/h	50km/h	10km/h	50km/h			
17.5R25 TL	★	14.00/1.5	448	1415	7100	4125	475	350	176A2	157B	L-5	64	JZ01
17.5R25 TL	★★	14.00/1.5	448	1415	8500	5450	600	475	182A2	167B	L-5	64	JZ01
20.5R25 TL	★	17.00/2.5	522	1492	9500	5600	475	350	186A2	168B	L-3	72	JZ01
20.5R25 TL	★★	17.00/2.5	522	1492	11500	7300	600	475	193A2	177B	E-3	72	JZ01
23.5R25 TL	★	19.50/2.5	600	1620	12150	7100	475	350	195A2	176B	L-3	80	JZ01
23.5R25 TL	★★	19.50/2.5	600	1620	14500	9250	600	475	201A2	185B	E-3	80	JZ01
26.5R25 TL	★	22.00/3.0	675	1750	15000	9000	475	350	202A2	184B	L-3D	95	JZ01
26.5R25 TL	★★	22.00/3.0	675	1750	18500	11500	600	475	209A2	193B	E-3D	95	JZ01
29.5R25 TL	★	25.00/3.5	750	1875	18000	10900	475	350	208A2	191B	L-3D	100	JS01C
29.5R25 TL	★★	25.00/3.5	750	1875	22400	14000	600	475	216A2	200B	E-3D	100	JS01C