



A2236

Usage: applied for loader, bulldozer as well as earthmover in varied working conditions, such like, mine, coal and sand yard.

Characteristic: with better cutting and wear-resisting performances; superior self-cleaning and side-sliding properties in muddy, soft and sliding working conditions, which could improve its self-cleaning, traction and operation stability.

SIZE	STAR RATING	RIM	NEW TYRE DIMENSION(mm)		LOAD(kg)		PRESSURE(kPa)		LI/SS		TRA CODE	TREAD DEPTH (mm)	VALVE
			WID.	DIA.	10km/	50km/h	10km/h	50km/h	10km/h	50km/h			
20.5R25 TL	★	17.00/2.	522	1492	9500	5600	475	350	186A2	168B	L-3	32	JZ01
20.5R25 TL	★★	17.00/2.	522	1492	11500	7300	600	475	193A2	177B	E-3	32	JZ01
23.5R25 TL	★	19.50/2.	600	1620	12150	7100	475	350	195A2	176B	L-3	36	JZ01
23.5R25 TL	★★	19.50/2.	600	1620	14500	9250	600	475	201A2	185B	E-3	36	JZ01



A2239

Usage: applied for loader, grader and excavator operating in poor road conditions like: mines, pit and construction site.

Characteristic: good anti-wearing and anti-cutting character, good traction and self cleaning character.

SIZE	STAR RATING	RIM	NEW TYRE DIMENSION(mm)		LOAD(kg)		PRESSURE(kPa)		LI/SS		TRA CODE	TREAD DEPTH (mm)	VALVE
			WID.	DIA.	10km/h	50km/	10km/	50km/h	10km/h	50km/			
20.5R25 TL	★	17.00/2.5	520	1572	9500		475		186A2		L-5	72	JZ01
20.5R25 TL	★★	17.00/2.5	520	1572	11500		600		193A2		L-5	72	JZ01
23.5R25 TL	★	19.50/2.5	600	1704	12150		475		195A2		L-5	78	JZ01
23.5R25 TL	★★	19.50/2.5	600	1704	14500		600		201A2		L-5	78	JZ01
26.5R25 TL	★	22.00/3.0	676	1805	15000		475		202A2		L-5S	95	JZ01
26.5R25 TL	★★	22.00/3.0	676	1805	18500		600		209A2		L-5S	95	JZ01