



A2237

Usage: applied for loader, bulldozer as well as dumper in poor working condition.

characteristic: wide and thick tread blocks can provide superior anti-cutting, anti-puncture, anti-wearing, anti-impact character, with better traction, mud draining and side-sliding properties, which improve it's self-cleaning, passing-through and operation stability character.

SIZE	STAR RATING	RIM	NEW TYRE DIMENSION(mm)		LOAD(kg)		PRESSURE(kPa)		LI/SS		TRA CODE	TREAD DEPTH (mm)	VALVE
			WID.	DIA.	10km/	50km/	10km/h	50km/h	10km/h	50km/h			
23.5R25 TL	★	19.50/2.5	600	1630	12150	7100	475	350	195A2	176B	L-3D	40	JZ01
23.5R25 TL	★★	19.50/2.5	600	1630	14500	9250	600	475	201A2	185B	E-3D	40	JZ01
26.5R25 TL	★	22.00/3.0	675	1750	15000	9000	475	350	202A2	184B	L-3D	45	JZ01
26.5R25 TL	★★	22.00/3.0	675	1750	18500	11500	600	475	209A2	193B	E-3D	45	JZ01
29.5R25 TL	★	25.00/3.5	750	1875	18000	10900	475	350	208A2	191B	L-3D	48	JS01C
29.5R25 TL	★★	25.00/3.5	750	1875	22400	14000	600	475	216A2	200B	E-3D	48	JS01C



A2238

Usage: Suitable to loading mechanical vehicles operating under many conditions
Characteristic: E4 deep tread pattern with high traction performance, Excellent design keep high speed ride in poor conditions

SIZE	STAR RATING	RIM	NEW TYRE DIMENSION(mm)		LOAD(kg)		PRESSURE(kPa)		TRA CODE	TREAD DEPTH (mm)	VALVE
			WID.	DIA.	10km/	50km/h	10km/h	50km/h			
18.00R33	★★	13.00/2.	495	1820	18500	10900	800	650	E-4	54	HZ01